



# Ronin-S Camera Compatibility List

2018.11.19 (for gimbal firmware v1.6.0.50)

The camera and lens combinations listed below can be physically balanced and stabilized on the Ronin-S. The Control Feature column indicates camera features that can be accessed by the gimbal and app. Cameras and lenses similar in size and weight may be compatible, but will not be listed until official verification by DJI. This list will be updated as more camera and lens setups are tested and verified.

Brand	Model	Cable	Control Feature	Camera Setup Method	Camera Firmware Version	Updates in Next Firmware	Compatible Lenses
Canon	6D MK II	RSS-IR (in the box)	Start/stop recording video Capture photo	Please switch to Self-timer mode and ensure Bluetooth is turned off	v1.0.3	1. Pulling focus electronically; 2. Half-pressing gimbal's Camera Control Button to trigger auto focus 3. Enhance system reliability when controlled via Canon SDK	
	5D MK III	RSS-IR (in the box) MCC-Mini (optional)	When using RSS-IR: Start/stop recording video Capture photo  When using MCC-Mini: Start/stop recording video Capture photo Pull focus electronically Trigger auto focus	Please switch to Self-timer mode  When using MCC- Mini: 1. Due to various lens focus control mechanisms, when using the Ronin-S to pull focus, you may need to switch the lens between AF and MF to see which best fits your need. 2. When switched to Photo mode, the camera won't respond to video-capturing commands; when switched to video mode, the camera won't respond to photo-capturing commands.	v1.3.5	/	EF 8-15mm f/4L USM EF 11-24mm f/4L USM EF 16-35mm f/2.8L III USM EF 16-35mm f/4L IS USM EF 17-40mm f/4L USM EF 24-70mm f/2.8L II USM EF 24-70mm f/4L IS USM EF 24-105mm f/4L IS II USM EF 24-105mm f/3.5-5.6 IS STM EF 35mm f/1.4L II USM EF 50mm f/1.2L USM EF 85mm f/1.2L II USM EF 85mm f/1.4L IS USM EF 85mm f/1.8 USM
	5D MK IV	RSS-IR (in the box) MCC-B (in the box)	When using RSS-IR: Start/stop recording video Capture photo  When using MCC-B: Start/stop recording video Capture photo Pull focus electronically Trigger auto focus	When using RSS-IR: Please switch to Self-timer mode  When using MCC-B: 1. Due to various lens focus control mechanisms, when using the Ronin-S to pull focus, you may need to switch the lens between AF and MF to see which best fits your need. 2. The camera's AF Servo should be shut off when pulling focus. 3. When switched to Photo mode, the camera won't respond to video-capturing commands; when switched to video mode, the camera won't respond to photo-capturing commands.	v1.1.2	Enhance system reliability when controlled via Canon SDK	
	EOS-1D X Mark II			1. Due to various lens focus control mechanisms, when using the Ronin-S to pull focus, you may need to switch the lens between AF and MF to see which best fits your need. 2. When switched to Photo mode, the camera won't respond to video-capturing commands; when switched to video mode, the camera won't respond to photo-capturing commands.	v1.1.3	/	
Panasonic	GH3	RSS-P (optional)	Start/stop recording video Capture photo	/	v1.1	/	
	GH4	RSS-P (optional)	Trigger auto focus		v2.6	/	H-E08018GK H-HSA35100GK H-HSA12035GK FSA45200GK H-ES12060GK H-X012GK H-FS12060GK H-H025GK H-X015GK H-HS030GK
	GH5/ GH5s	MCC-C (in the box)	Start/stop recording video Capture photo Pull focus electronically Trigger auto focus	1. Choose PC (Tether) mode upon connection; 2. To pull focus with Ronin-S, the focus mode toggle on the camera should be set to MF; 3. To trigger camera's auto focus, half press the Camera Control button on the gimbal and ensure the camera's focus mode is set to AFS/AFF/AFC.	GH5: v2.2 GH5s: v1.1	Resolve camera freeze issue occurs when the camera is in playback mode	
Nikon	D850	MCC-B (in the box)	Start/stop recording video Capture photo Pull focus electronically Trigger auto focus	1. Please ensure live view on camera stays on when used with Ronin-S; 2. When connected with MCC-B cable, the built-in dials and buttons on camera will be locked; 3. To pull focus with Ronin-S, please set the lens focus mode to M/A, and make sure the camera focus mode is set to AF. 4. Gimbal's range of motion might be restricted when a longer lens is mounted, please setup the gimbal's control Endpoints and SmoothTrack parameters to avoid unintentional collision of equipments.	v1.00	/	AF-S NIKKOR 14-24mm f/2.8G ED AF-S NIKKOR 16-35mm f/4G ED VR AF-S Zoom-NIKKOR 17-35mm f/2.8D IF-ED AF-S NIKKOR 18-35mm f/3.5-4.5G ED AF-S NIKKOR 24-70mm f/2.8E ED VR AF-S NIKKOR 24-70mm f/2.8G ED AF Zoom-NIKKOR 24-85mm f/2.8-4D IF AF-S NIKKOR 24-85mm f/3.5-4.5G ED VR AF-S NIKKOR 24-120mm f/4G ED VR AF-S NIKKOR 28-300mm f/3.5-5.6G ED VR AF NIKKOR 14mm f/2.8D ED AF-S NIKKOR 20mm f/1.8G ED AF-S NIKKOR 24mm f/1.4G ED AF-S NIKKOR 24mm f/1.8G ED AF-S NIKKOR 50mm f/1.4G AF-S NIKKOR 85mm f/1.4G AF-S NIKKOR 85mm f/1.8G
	D5				v1.21	/	
	Z7	MCC-C (in the box)			v 1.01	/	NIKKOR Z 24-70mm f/4S NIKKOR Z 50mm f/1.8S NIKKOR Z 35mm f/1.8S
Sony	A7 S	RSS-IR (in the box) MCC-Multi (optional)	Start/stop recording video Capture photo  When using RSS-IR: Start/stop recording video Capture photo  When using MCC-Multi: Start/stop recording video Capture photo Zoom control (digital or optical) Trigger auto focus	When using RSS-IR: 1. Please turn on the Remote function in camera; 2. When using Create features, please turn off Auto Review to enhance camera operating efficiency.  When using MCC-Multi: 1. After connecting the cable, be sure to power on the Ronin-S before the camera. Otherwise, the Ronin-S does not recognize the camera. If the camera is not recognized, restart the camera or remove and reconnect the cable to the camera. 2. The optical zoom can be controlled through the Ronin-S Focus Wheel (only lenses with built-in power zoom, such as the Sony E PZ 18-105 mm F4 G OSS). If a non-Power Zoom lens is mounted, the Focus Wheel will control digital zoom. Digital zoom must be enabled in your camera's settings. 3. After connecting with a Sony camera using the MCC-Multi cable, if you need to swap to a camera of other manufacturers then a gimbal reboot is required.	V3.20	/	FE 24-105 mm F4 G OSS FE 16-35mm F2.8 GM FE 12-24mm F4 G FE 100mm F2.8 STF GM OSS FE 85mm F1.8 Vario-Tessar T* FE 16-35 mm F4 ZA OSS FE 24-70 mm F2.8 GM Vario-Tessar T* FE 24-70 mm F4 ZA OSS FE 28-70 mm F3.5-5.6 OSS FE 28 mm F2 Distagon T* FE 35 mm F1.4 ZA Sonnar T* FE 35 mm F2.8 ZA Planar T* FE 50mm F1.4 ZA FE 50mm F1.8 Sonnar® T* FE 55 mm F1.8 ZA FE 85 mm F1.4 GM FE 90 mm F2.8 Macro G OSS
	A7 II				v4.00		
	A7S II				v3.00		
	A7 RII				v4.00		
	A7 III				v1.01		
	A7R III				v1.10		
	A9				V3.10		
	A6000				V3.20		
	A6300				v1.10		
	A6500				V1.05		

The camera and lens combinations listed below can be physically balanced and stabilized on the Ronin-S. We will continuously look into possibilities of bringing more features to more camera models.

Brand	Model	Follow-up Development Plan	Brand	Model	Follow-up Development Plan
Canon	60D, 70D, 77D, 80D, 7D series	Continue improving RSS-IR cable reliability; Developing USB shutter control to more camera models	Nikon	D810, D7500, D500, D800, D810A, D3, D300, D300S, D3S, D3X, D4, D4S, D600, D610, D700	Developing USB shutter control
Sony	A9, A7 series	Improving RSS-IR cable reliability; Developing USB shutter control		D5000, D5100, D5200, D5300, D5500, D7000, D7100, D7200, D750, D90, Df	Developing IR shutter control
			Hasselblad	X1D	Developing USB shutter control

- ⚠ Certain camera models will slow down its focus process in low-light conditions; we recommend using manual focus when a Create feature is used.
- Please turn off Auto Review (Sony) or Image Review (Canon) when used with a Create feature.
- A redesigned lens control motor will be released soon.